

Karta techniczna


Zestaw integracyjny PZA R6003

Aluminiowy profil
okrągły $\varnothing 89$ mm



Skład zestawu:

1. Wieża bez dachu z podestem kwadratowym na wys. 48 cm - 2 szt.
2. Wieża bez dachu z podestem kwadratowym na wys. 78 cm - 1 szt.
3. Wieża bez dachu z podestem trójkątnym na wys. 78 cm - 1 szt.
4. Wieża bez dachu z podestem kwadratowym na wys. 108 cm - 1 szt.
5. Wieża bez dachu z podestem trójkątnym na wys. 150 cm - 1 szt.
6. Wieża z dachem dwuspadowym z podestem kwadratowym na wys. 150 cm - 1 szt.
7. Mostek łukowy skośny - 4 szt.
8. Mostek równoważnia - 1 szt.
9. Podjazd dla wózków inwalidzkich - 2 szt.
10. Zjeżdżalnia na podest 150 cm - 1 szt.
11. Wejście talerzykowe - 1 szt.
12. Pionowa ścianka wspinaczkowa - 1 szt.
13. Przeplotnia - 1 szt.
14. Drążek do podciągania - 1 szt.
15. Panel edukacyjny "Sklepik" - 1 szt.
16. Gra edukacyjna "Kółko i krzyżyk" - 1 szt.




1400 [cm]

Przedział wiekowy: 3+

Strefa bezpieczeństwa: 1700 cm x 1375 cm

Powierzchnia strefy bezpieczeństwa: 129 m²

Wysokość swobodnego upadku: 200 cm



Montaż:

Zestaw zamontowany w gruncie.
Fundamenty wykonywane z betonu klasy B-25.

Mounting:

The set is mounted in the ground.
Foundations made of C20/25 concrete.

In sets containing a slide, pay attention to the location in relation to the directions of the world because the sun heats the slide. The slide should not be mounted to the south.

Acceptable shock absorbing surfaces and their minimum thickness

Material ^a	Description [mm]	Minimum depth ^b [cm]	Maximum free heights of fall [cm]
Turf/topsoil		-	≤ 100 ^d
Bark	20 to 80 particle size	20	≤ 200
		30	≤ 300
Woodchip	5 to 30 particle size	20	≤ 200
		30	≤ 300
Sand or gravel ^c	0,25 to 8 grain size	20	≤ 200
		30	≤ 300
Other materials	As tested according to EN 1177		Critical fall height as tested

^a For further information on specific material properly prepared for use in children's playgrounds

^b For loose particulate material, add 100 mm to the minimum depth to compensate for displacement (see 4.2.8.5.1).

^c Sand and gravel shall be well rounded and washed to eliminate most of the silt or clay particles. Washed sand and gravel is considered to be from alluvial (natural eroded) deposits and free from most silt or clay particles. For gravel this may commonly be described as 'pea shingle'. Uniformity coefficient $D_{60}/D_{10} < 3,0$. Grain size can be identified by use of a sieve test, as in EN 933-1 (see Annex G)

^d See NOTE 2 in 4.2.8.5.2